



Catalog number:	TRAIL150N	TRAIL150NE (emergency)
Power consumption:	25-75W	25-75W
Luminous Flux:	3877-11523lm	3877-11523lm
Dimensions w x h x d:	65 x 45 x 1437mm	65 x 45 x 1437mm
Optics:	30°, 60°, 90°, 120°, 20° asy.	30°, 60°, 90°, 120°, 20° asy.
Weight:	3,9kg	3,9kg
Light Color:	4000K	4000K
Guarantee:	60 months	60 months
Dimming:	0-10V, DALI	0-10V, DALI

Luminaire parameters

Working voltage	AC 100-277V
Operating temperature	-30° to +50°
Material	sheet metal
Mounting	suspension after 2.3 m
Diode type	Edison
Driver	ENEC DIP switches
Number of conductors in the profile	8x2.5mm2 12x2.5mm2 (for variant with CBS)
Diffuser material	PMMA, PC plastic
Surface Finish	powder dye
Construction color	white
Service life	50,000 hours
Color Rendering Index	Ra>80
Power factor PF	>0.9
Degree of coverage	IP40, IP54
Dimming	DALI, 0-10V

Carrier power profile	1437mm, 2874mm
Emergency module	2 h.
Accessories	Motion sensor, Daylight sensor, Tracklight adapter

